



Ordering Information

SFP Optical Transceivers, 1.25GBit

RLH - SFP - XX -1

Configuration Code

Code	Multimode	Single Mode	Single Fiber Bi-Directional	Dual Fiber	SC Connector	LC Connector	0.5km/0.3mi. range	2km/1.25mi. range	20km/12.4 mi. range	40km/24.9 mi. range	60km/37 mi. range	80km/50 mi. range	Tx 850nm/Rx 1300nm	Tx 1300nm/Rx850nm	1310/1550nm
01	●		●		●			●					●		
02	●		●		●			●						●	
03	●			●		●	●								●
10		●	●		●			●					●		
11		●	●		●			●						●	
12		●	●		●				●				●		
13		●	●		●				●					●	
14		●	●		●					●			●		
15		●	●		●					●				●	
20		●	●			●			●				●		
21		●	●			●			●					●	
22		●	●			●				●			●		
23		●	●			●				●				●	
30		●		●		●			●						●
31		●		●		●					●				●
32		●		●		●						●			●

- ▶ For bidirectional single fiber models, Tx wavelength must match the Rx wavelength of connecting equipment, and conversely, Rx wavelength must match Tx wavelength of connecting equipment.
- ▶ Bidirectional optic wavelength may be special ordered. Contact factory for availability.
- ▶ Please contact your RLH sales representative for pricing and delivery information.