

Ordering Information

RLH 4+4 Port Managed Industrial Ethernet Fiber Switch, DIN/Wall Mount

RLH - ESM44 - XX -1

See Configuration Code

	Config. Code	Single Fiber Bi-Directional	Dual Fiber	Connector			Wavelength				Range						
				SC	ST	FC	850nm	1310nm	1550nm	A Tx 1310nm Rx 1550nm	B Tx 1550nm Rx 1310nm	2km/1.25 mi.	20km/12.4 mi.	40km/24.9 mi.	60km/37 mi.	120km/74 mi.	
Multimode	01	•		•						•							
	02	•		•							•						
	03		•	•								•					
	04				•				•								
	05		•			•											
	06		•	•				•									
	07		•			•											
	08		•				•										
Single Mode	10	•		•							•						
	11	•		•								•					
	12	•		•									•				
	13	•		•										•			
	14	•		•											•		
	15	•		•												•	
	20	•			•												•
	21	•				•											
	22	•															
	23	•				•											
	24	•					•										
	25	•															
	30	•															
	31	•															
	32	•															
	33	•															
	34	•															
	35	•															
	40		•	•													
	41		•	•													
	42		•	•													
	43		•	•													
	44		•	•													
	45		•	•													
	50		•			•											
	51		•														
	52		•														
	53		•														
54		•															
55		•															
60		•															
61		•															
62		•															
63		•															
64		•															
65		•															

- ▶ Bidirectional single fiber models require an A Side and B Side unit for a complete system.
- ▶ Bidirectional optic wavelength may be special ordered. Contact factory for availability.
- ▶ Please contact your RLH sales representative for pricing and delivery information.

Specifications subject to change without notice.