Ordering Information

RLH POTS FIBER MUX SYSTEM
2 Channel Analog Phone with Ethernet over Fiber

RLH - PM2 - [XX] - [X] [X] -2

See Configuration Code

Side
C = FXO/CO side
S = FXS/Sub side

Style
D = DIN/wall mount
P = 4RU Plug-in Card

	Config. Code	Single Fiber Bi-Directional	Dual Fiber	Connector: SC	Connector: ST	Connector: FC	Wavelength: 850nm	Wavelength: 1310nm	Wavelength: 1550nm	Wavelength: Tx 1310nm Rx 1550nm	Wavelength: Tx 1550n Rx 1310nm	Range: 0.5km/0.3 mi.	Range: 2km/1.25 mi.	Range: 20km/12.4 mi.	Range: 40km/24.9 mi.	Range: 60km/37 mi.	Range: 120km/74 mi.
Multimode	01	●		●						●			●				
	02	●		●							●		●				
	03		●	●				●					●				
	04		●		●			●					●				
	05		●			●		●					●				
	06		●	●			●					●					
	07		●		●		●					●					
	08		●			●	●					●					
Single Mode	10	●		●						●				●			
	11	●		●							●			●			
	12	●		●						●					●		
	13	●		●							●				●		
	14	●		●						●						●	
	15	●		●							●					●	
	20	●			●					●				●			
	21	●			●						●			●			
	22	●			●					●					●		
	23	●			●						●				●		
	24	●			●					●						●	
	25	●			●						●					●	
	30	●				●				●				●			
	31	●				●					●			●			
	32	●				●				●					●		
	33	●				●					●				●		
	34	●				●				●						●	
	35	●				●					●					●	
	40		●	●				●						●			
	41		●	●				●								●	
	42		●	●				●									●
	43		●	●					●					●			
	44		●	●					●							●	
	45		●	●					●								●
	50		●		●			●						●			
	51		●		●			●								●	
	52		●		●			●									●
	53		●		●				●					●			
	54		●		●				●							●	
	55		●		●				●								●
	60		●			●		●						●			
	61		●			●		●								●	
	62		●			●		●									●
	63		●			●			●					●			
	64		●			●			●							●	
	65		●			●			●								●

- Example: **RLH-PM2-01-CD-2**
  RLH 2x1 POTS mux configured as multimode, single bi-directional fiber, SC connector, 2km/1.25mi. range, DIN/wall mount style, FXO/CO side configuration.
- 4RU plug-in card models includes RJ-11 breakout adapter for easy connection to existing POTS lines
- A complete system requires a FXO/CO and a FXS/Sub unit
- Please contact your RLH sales representative for pricing and delivery information