



# Ordering Information

RLH RS-232 Serial Data Over Fiber System

RLH - RD - **XX** **X** -1

See Configuration Code

A = 115/220VAC Power Adapter

U = 24VDC Power Adapter

V = 48VDC Power Adapter

	Config. Code	Fiber		Connector			Wavelength				Range							
		Single Fiber Bi-Directional	Dual Fiber	SC	ST	FC	850nm	1310nm	1550nm	Tx 1310nm Rx 1550nm	Tx 1550nm Rx 1310nm	0.5km/0.3 mi.	2km/1.25 mi.	20km/12.4 mi.	40km/24.9 mi.	60km/37 mi.	120km/74 mi.	
Multimode	01	•		•						•								
	02	•		•						•								
	03		•	•														
	04		•		•				•									
	05		•			•			•									
	06		•	•	•													
	07		•			•			•									
	08		•				•		•									
Single Mode	10	•		•						•				•				
	11	•		•						•	•			•				
	12	•		•						•					•			
	13	•		•						•	•				•			
	14	•		•						•						•		
	15	•		•						•	•					•		
	20	•			•					•				•				
	21	•				•				•	•			•				
	22	•				•				•				•				
	23	•				•				•	•			•				
	24	•				•				•					•			
	25	•				•				•	•					•		
	30	•					•			•				•				
	31	•					•			•	•			•				
	32	•					•			•				•				
	33	•					•			•	•			•				
	34	•					•			•					•			
	35	•					•			•	•					•		
	40		•	•	•				•					•				
	41		•	•	•				•					•			•	
	42		•	•	•				•					•				
	43		•	•	•					•				•				
	44		•	•	•					•				•			•	
	45		•	•	•					•				•				
	50		•	•		•				•				•				
	51		•	•		•				•				•			•	
	52		•	•		•				•				•				
53		•	•						•				•					
54		•	•		•				•				•			•		
55		•	•		•				•				•					
60		•				•			•				•					
61		•				•			•				•			•		
62		•				•			•				•					
63		•				•			•				•					
64		•				•			•				•			•		
65		•				•			•				•					

► Please contact your RLH sales representative for pricing and delivery information