



Ordering Information

RLH RS-232/422/485 Serial Data Over Fiber System

RLH - SD - XX -1

See Configuration Code

	Config. Code 	Single Fiber Bi-Directional	Dual Fiber	Connector			Wavelength					Range						
				SC	ST	FC	850nm	1310nm	1550nm	Tx 1310nm Rx 1550nm	Tx 1550nm Rx 1310nm	0.5km/0.3 mi.	2km/1.25 mi.	20km/12.4 mi.	40km/24.9 mi.	60km/37 mi.	120km/74 mi.	
Multimode	01	•		•							•							
	02	•		•							•							
	03		•	•					•									
	04		•	•	•				•									
	05		•	•		•			•									
	06		•	•	•		•											
	07		•	•		•	•											
	08		•	•		•	•											
Single Mode	10	•		•							•					•		
	11	•		•							•					•		
	12	•		•							•					•		
	13	•		•							•				•			
	14	•		•							•					•		
	15	•		•							•					•		
	20	•			•							•				•		
	21	•			•							•				•		
	22	•			•							•				•		
	23	•			•							•			•			
	24	•			•							•				•		
	25	•			•							•				•		
	30	•					•					•				•		
	31	•					•					•				•		
	32	•					•					•			•			
	33	•					•					•			•			
	34	•					•					•			•			
	35	•					•					•			•			
	40		•		•				•							•		
	41		•		•				•							•		
	42		•		•				•							•		
	43		•		•				•							•		
	44		•		•				•		•					•		
	45		•		•				•		•					•		
	50		•		•				•						•			
	51		•		•				•						•			
	52		•		•				•						•			•
53		•		•				•						•				
54		•		•				•						•				
55		•		•				•						•			•	
60		•				•								•				
61		•				•								•				
62		•				•								•			•	
63		•				•								•				
64		•				•								•				
65		•				•								•			•	

► Please contact your RLH sales representative for pricing and delivery information