

Ordering Information

Single Channel Mini Video (MV) Over Fiber Unit

Stand Alone/Wall Mountable



Mini Converter Part Number Matrix

RLH - MV - **XX** **XX** - **X** **X** **X** - 01

Fiber Type

MM = Multimode, 2km range, Dual Fiber
 MB = Multitmode, 2km range, Bi-Di (SC Only)
 S1 = Single Mode, 20km range, Dual Fiber
 S2 = Single Mode, 20km range, Bi-Di
 S3 = Single Mode, 40km range, Bi-Di
 S4 = Single Mode, 60km range, Dual Fiber
 S5 = Single Mode, 60km range, Bi-Di
 S6 = Single Mode, 120km range, Dual Fiber

Fiber Connector Style

ST = ST Connector
 SC = SC Connector
 FC = FC Connector

TX/RX

T = Transmitter
 R = Receiver

Powering Option

A = 115VAC power adapter
 U = 24VDC power adapter
 V = 48VDC power adapter

Port Option

N = None
 B = Bi-directional Data RS232
 C = Bi-directional Data RS422
 F = Bi-directional Data RS485
 D = Single Way Data RS232
 G = Single Way Data RS422
 H = Single Way Data RS485
 A = Bi-directional Audio
 R = Reverse Audio
 E = Ethernet 10/100
 T = Analog Telephone
 S = I/O Switch (Contact Closure)

Example: RLH-MV-S1ST-BAT-01

Mini Video Converter, single mode fiber 20km range, ST connector, bi-directional RS-232 data port, 115VAC, transmitter module.

- ▶ A complete system requires 1 Transmitter unit and 1 Receiver unit
- ▶ Please contact your RLH sales representative for pricing and delivery information