


T1 Product Family

4RU Single Channel Plug-in Card

- Temperature hardened
- Line powered or local powered
- 4RU Plug-in Card fits in any RLH card housing
- Distances up to 60km/37 miles



4RU 4 Channel Mux Plug-in Card

- Temperature hardened
- Line powered or local powered
- 4RU Plug-in Card fits in any RLH card housing
- Distances up to 60km/37 miles



4RU Single Channel DS3/T3 Plug-in Card

- Temperature hardened
- Local 24~56VDC powered
- 4RU Plug-in Card fits in any RLH card housing
- Distances up to 60km/37 miles

iMux Modular Multiplexer

- Up to 16 Channels of T1 in 1RU 19" rack mount chassis
- Options include E1, RS-232 data, Analog Phone (POTS), 2/4 Wire Analog Data/Audio/SCADA/E&M
- Hot swappable, 1+1 protected optical modules
- Dual or single bi-directional fiber models
- Managed through software, web interface or front panel
- Integrated 115VAC or 48VDC power supplies
- Distances up to 120km/74 miles



16x1 T1 over Ethernet Multiplexer

- 16 Channels of T1 in 1RU 19" rack mount chassis
- Five 10/100/1000M Ethernet ports, one Gigabit SFP slot
- Managed through software or web interface
- Dual redundant, field replaceable, 115VAC or 48VDC power supplies
- Distances up to 120km/74 miles



Contact your RLH Sales Representative for additional information