

ORDERING INFORMATION

www.fiberopticlink.com

OI-M005 2021-12-11

Fiber Optic Patch Cords

A Wide Variety of Riser and Plenum Patch Cords Available

High-quality, custom, fiber patch cords for the Telecom, CATV, and Datacom industries. Patch Cords are ideal for short distance patching applications. Each patch cord is fully tested to meet or exceed industry requirements.

Key Features

- Meets Telcordia GR-326, IEC, TIA/EIA requirements
- Each patch cord is 100% tested and certified
- RoHS compliant
- Individually packaged or wound on reels
- Any style custom patch cords upon request



Ordering Information

RLH – J A B C D – E F – G H

A - # of Fibers
S = Simplex
D = Duplex

B - Jacket
R = Riser (OFNR)
P = Plenum (OFNP)
L = LSZH

C - Diameter
3 = 3mm
2 = 2mm
1 = 1.6mm

E - Connector 1
ST = ST
SC = SC
SD = SC D*
SA = SC/APC
SB = SC/APC D*
LC = LC
LD = LC D*
LA = LC/APC
LB = LC/APC D*
FC = FC
FA = FC/APC

MU = MU
MA = MU/APC
MJ = MTRJ M*
MF = MTRJ F*
E2 = E2000
EA = E2000/APC
D4 = D4
FD = FDDI
ES = ESCON
S5 = SMA905
S6 = SMA906

F - Connector 2
ST = ST
SC = SC
SD = SC D*
SA = SC/APC
SB = SC/APC D*
LC = LC
LD = LC D*
LA = LC/APC
LB = LC/APC D*
FC = FC
FA = FC/APC

MU = MU
MA = MU/APC
MJ = MTRJ M*
MF = MTRJ F*
E2 = E2000
EA = E2000/APC
D4 = D4
FD = FDDI
ES = ESCON
S5 = SMA905
S6 = SMA906
PT = Pigtail

G - Total Length
= Length

H - Unit of Measure
F = Feet
M = Meters

M* = Male with pins, F* = Female no pins, D* = With duplex clip

D - Fiber Types
SM = Singlemode (8~9/125)
SB = Singlemode (8~9/125) bend insensitive
MM = Multimode (62.5/125, OM1)
M5 = Multimode (50/125, OM2)
MX = Multimode 10G (50/125, OM3)
MC = Multimode 10G (50/125, OM4)
MV = Multimode 40/100G (50/125, OM5)

◆ Please contact an RLH sales representative for cable/connector types not listed and for pricing/delivery information