

## ORDERING INFORMATION

[www.fiberopticlink.com](http://www.fiberopticlink.com)

OI-M005 2020-05-18

### Fiber Optic Patch Cords

#### A Wide Variety of Riser and Plenum Patch Cords Available

High-quality, custom, fiber patch cords for the Telecom, CATV, and Datacom industries. Patch Cords are ideal for short distance patching applications. Each patch cord is fully tested to meet or exceed industry requirements.

#### Key Features

- ◆ Meets Telcordia GR-326, IEC, TIA/EIA requirements
- ◆ Each patch cord is 100% tested and certified
- ◆ RoHS compliant
- ◆ Individually packaged or wound on reels
- ◆ Any style custom patch cords upon request



### Ordering Information

RLH – J A B C D – E F – G H

- A - # of Fibers**
- S = Simplex  
D = Duplex
- B - Jacket**
- R = Riser (OFNR)  
P = Plenum (OFNP)  
L = LSZH
- C - Diameter**
- 3 = 3mm  
2 = 2mm  
1 = 1.6mm

- E - Connector 1**
- |                |                |
|----------------|----------------|
| ST = ST        | MU = MU        |
| SC = SC        | MA = MU/APC    |
| SD = SC D*     | MJ = MTRJ M*   |
| SA = SC/APC    | MF = MTRJ F*   |
| SB = SC/APC D* | E2 = E2000     |
| LC = LC        | EA = E2000/APC |
| LD = LC D*     | D4 = D4        |
| LA = LC/APC    | FD = FDDI      |
| LB = LC/APC D* | ES = ESCON     |
| FC = FC        | S5 = SMA905    |
| FA = FC/APC    | S6 = SMA906    |

- F - Connector 2**
- |                |                |
|----------------|----------------|
| ST = ST        | MU = MU        |
| SC = SC        | MA = MU/APC    |
| SD = SC D*     | MJ = MTRJ M*   |
| SA = SC/APC    | MF = MTRJ F*   |
| SB = SC/APC D* | E2 = E2000     |
| LC = LC        | EA = E2000/APC |
| LD = LC D*     | D4 = D4        |
| LA = LC/APC    | FD = FDDI      |
| LB = LC/APC D* | ES = ESCON     |
| FC = FC        | S5 = SMA905    |
| FA = FC/APC    | S6 = SMA906    |
|                | PT = Pigtail   |

- G - Total Length**
- ## = Length
- H - Unit of Measure**
- F = Feet  
M = Meters

M\* = Male with pins, F\* = Female no pins, D\* = With duplex clip

- D - Fiber Types**
- SM = Singlemode (8~9/125)  
SB = Singlemode (8~9/125) bend insensitive  
MM = Multimode (62.5/125, OM1)  
M5 = Multimode (50/125, OM2)  
MX = Multimode 10G (50/125, OM3)  
MC = Multimode 10G (50/125, OM4)  
MV = Multimode 40/100G (50/125, OM5)

◆ Please contact an RLH sales representative for cable/connector types not listed and for pricing/delivery information