fiberopticlink.com



DS-201 2025-0618

12 Fiber MTP Cable Assemblies - Indoor/Outdoor Riser

Rugged, Factory Terminated and Certified

RLH MTP cable assemblies are designed for both indoor and outdoor environments by incorporating a UV rated jacket with Riser (OFNR) flame rating. This dual purpose cable offers convenient and cost effective solution for cable routes spanning a variety of environments by eliminating the need for transition splicing to an indoor-rated cable when routing into the building.

RLH Indoor/Outdoor MTP cable assemblies are factory terminated and can be ordered in any length required. Cable assemblies include a pull sheath for ease of deployment. Each assembly is fully tested and includes a certification test report.


12 Fiber, MTP Cable Assembly with 1 pulling sheath

Application

- Riser (OFNR) Inside and Outside Plant
- Campus LAN
- Building Interconnections
- Mining

Features

- Factory terminated and certified to GR-1435, IEC 61300-3-35
- Pre-installed pulling sheath
- UV and Moisture Resistant outer jacket
- Quick field installation



MTP Singlemode Connectors



General Specifications

Fiber Count	12 Strand		
Fiber Type	Singlemode OS2 (8-9/125) Multimode OM1(62.5/125) Multimode OM3 (50/125)		
Cable Type	Indoor/Outdoor with UV Protection		
Jacket Rating	Riser OFNR (UL 1666)		
Max. Attenuation	Singlemode (1310/1550nm): 0.5/0.4 dB/km Multimode OM1 (850/1300nm): 3.5/1.5 dB/km Multimode OM3 (850/1300nm): 3.0/1.5 dB/km		
Cable Outside Diameter	0.20" +/- 0.02"		
Bending Radius	Installation 15X O.D; Long Term 10X O.D.		
Approx. Weight	20lbs/kft +/- 10%		
Operating Temp.	-40°C to +70°C		
Recommended Conduit Size	1.0" minimum		
Connector Type	MTP/Female, Multimode: Flat (PC), Singlemode: Angled (APC)		
Max. Insertion Loss	Multimode: 0.5dB, Singlemode:0.75dB		
Polarity	Method A (Straight Through)		
Breakout	3.0mm – 18"		
Compliance	GR-1435, IEC 61300-3-35, RoHS		

Ordering Information

Fibers	Connectors	Mode	Rating	Breakout	Part Number
12	MTP Female	Singlemode	Riser OFNR	18 inch	RLH-12CRSM3-MSMS-B18-F-1-A
12	MTP Female	Multimode (OM1)	Riser OFNR	18 inch	RLH-12CRMM3-MLML-B18-F-1-A
12	MTP Female	Multimode (OM3)	Riser OFNR	18 inch	RLH-12CRMX3-MLML-B18-F-1-A
12	MTP Female	Multimode (OM4)	Riser OFNR	18 inch	RLH-12CRMC3-MLML-B18-F-1-A

^{• *}Specify desired cable length in Feet: "xxxxF"

Contact

By Mail	ATTN: Sales			
	RLH Industries, Ir 936 N. Main Stree Orange, CA 9286	et		
By Phone:	Local	714-532-1672		
Sales/Service	Toll Free	800-877-1672		
By email:	info@fiberopticlinl	info@fiberopticlink.com		
By Fax:	714-532-1885			

Support

By email:	support@fiberopticlink.com		
By Phone:	Toll Free 855-754-2497		