The leader in rugged, fiber optic technology

DATA SHEET

www.fiberopticlink.com

DS-M029 2024-06-20

Fusion Splice Protection Sleeves

40 mm & 60 mm Lengths

RLH Fusion Splice protection sleeves offer durable and long lasting protection for single fiber splices. A stainless steel rod is included to help provide rigidity and stability to your fusion splice. A fiber splice sleeve is added prior to splicing a fiber. Once spliced a heater will shrink the diameter down to 2.6 mm over the splice for protection.

Key Features

- Slim diameter, 2.6 mm
- Stainless steel rod for increased protection
- Fits RLH splice trays and holders
- Available in 40 mm & 60 mm sizes

Fusion Splice Protection Sleeves

Specifications

Sleeve Diameter After Shrink: 2.6 mm

Strength Member: Stainless Steel

Lengths: 40 mm or 60 mm (varies

by part number)

For Fiber Strands Sized: 250 to 900μm

Ordering Information

Description	Quantity	Part Number
40 mm Fusion Splice Protection Sleeves	15	FUSIONSS-40MM-015
40 mm Fusion Splice Protection Sleeves	30	FUSIONSS-40MM-030
40 mm Fusion Splice Protection Sleeves	100	FUSIONSS-40MM-100
60 mm Fusion Splice Protection Sleeves	30	FUSIONSS-60MM-030
60 mm Fusion Splice Protection Sleeves	100	FUSIONSS-60MM-100

40 mm Sleeve Compatibility

- RLH-FST-01
- RLH-FST-03
- RLH-FSH-04

60 mm Sleeve Compatibility

- RLH-FST-01
- RLH-FST-04
- RLH-FSH-04