

DATA SHEET

www.fiberopticlink.com

DS-M044 2024-08-28

Industrial 100 Watt 12V to 24V DC/DC Converter

Industrial, Rugged, & Compact

The RLH DC/DC converter is a compact power supply designed to convert a DC Input voltage to a regulated and isolated DC output voltage. Able to power a wide range of industrial equipment, this power supply offers a wide variety of conversion options to accommodate standard voltages found in substations, Telco, and automation & control environments.

This rugged power supply features a tough aluminum alloy frame with a powder-coated, galvanized-steel housing for superior corrosion resistance. The DIN clip allows for easy mounting anywhere DIN rail can be placed.

Supports a wide input voltage range and also allows for adjusting the output voltage to $\pm 10\%$ of the rated output voltage. The converter has a bi-color LED indicator and a relay output to indicate power status and alarm conditions.

Key Features


- Hardened to operate in -40°C to $+70^{\circ}\text{C}$ environment
- DIN mountable - install anywhere rail can be placed or found
- Bi-Color LED provide power status and alarm indication
- Sturdy powder-coated aluminum case
- Alarm relay output for remote/external monitoring
- High DC input available for converting large battery array power to usable range for network devices
- Isolated DC Output with $\pm 10\%$ adjustment

Ordering Information

Description	Input Voltage	Output Voltage	Amps	Part Number
100 Watt 12V to 24V DC/DC Converter	12VDC (9~18V)	24VDC	4.2A	RLH-D100-DCDC-1224-1



Industrial 100 Watt 12V to 24V DC/DC Converter



Dimensions

DATA SHEET

www.fiber opticlink.com


Key Specifications

Input:	Voltage Range	9 ~ 18V
Output:	Voltage	24V
	Start Time	10mS (Non capacitive Load)
	Voltage Accuracy	± 1.5% Max.
	Line Regulation	± 0.2% Max.
	Load Regulation	± 0.2% Max.
	Ripple & Noise	100mV RMS, 240mV pk-pk Max.
	Short Circuit Protection	Continuous
	Over Current Protection	110% - 140% Nominal Output
	Over Voltage Protection	115% - 140% Nominal Output
	Transient Response (25% Step Load Change)	< 500µs
	Output Voltage Trim	± 10%
General:	Switching Frequency	250KHz
	Efficiency	Up to 89.5%
	Operating Temperature	-40°C to +70°C
	Relative Humidity	95% RH Max., non-condensing
	Isolation Resistance	10MΩ Min.
	Input Polarity Reversal Protection	Diode or Relay Protection
	Input Over Voltage Protection	120% of max. input voltage
	Cooling	Heatsink, Convection cooling
	Isolation Voltage	Input to Output: 1500VDC
Alarm Relay:	Rated Load	0.50 A @ 125 VAC, 1A @ 24 VDC
	Max. Operating Voltage	125 VAC, 60 VDC
	Max. Operating Current	1A
	Max. Switching Capacity	62.50 VA, 30W
	RED Power LED - Relay Open	< 21.6VDC Output
	GREEN Power LED - Relay Closed	Normal Operation
	Power LED OFF - Relay Open	No Power Detected
Physical:	Dimensions	2.59" (W) x 3.79" (D) x 4.95" (H), (66mm x 97mm x 126mm)
	Weight	1.5 lbs.
	Construction	Aluminum alloy, galvanized steel, powder coated
	Mounting	35mm DIN rail

DATA SHEET

www.fiberopticlink.com

Typical Derating Curve



Contact

By Mail:	Att: Sales RLH Industries, Inc. 936 N. Main St. Orange, CA 92867
----------	---

By Phone: Sales / Service Mon - Fri, 6am - 6pm, PST	Local 714-532-1672
	Toll Free 800-877-1672 866-DO-FIBER

By Email:	info@fiberopticlink.com
-----------	--

By FAX:	714-532-1885
---------	--------------

Tech Support

By Email:	support@fiberopticlink.com
-----------	--

By Phone:	Toll Free 855-754-2497 855-RLH-24X7
-----------	---