

DATA SHEET

www.fiberopticlink.com

DS-M101 2023-09-04

Semi-Buried Pedestal (Type-07)

Semi-Buried Pedestal Enclosure

RLH Type-07 Semi-Buried Pedestals are tough, outdoor rated, all-dielectric equipment pedestals that include a treated plywood backboard, lockable covers with hex head self-locking system, and padlock hasp. The pedestal stands approximately 36" tall when the base is buried. No mounting stakes or platforms are required for installation.

These pedestals have enough room to install a 12-Card Fiber Optic Link housing in addition to other telecommunications equipment. Several housings may be mounted inside a single pedestal for high density applications. Pedestals are constructed of all-dielectric plastic with a steel support frame.

RLH offers standard Fiber Optic Link configurations pre-installed into enclosures. These Telco Interface Units allow for faster and more uniform field installations (see Ordering tab).

Key Features

- All-dielectric construction
- Internal steel frame
- Fire treated and painted $\frac{3}{4}$ " plywood backboard
- Self-locking cover with hex head release
- Spring latch and padlock locking hasp
- Ground lug connections
- Snap-Lock connection terminal with feedback loop tool
- 7" mounting depth on front of backboard (RLH side)
- 8" mounting depth on back of backboard (Telco Side)
- Available in 5-, 8-, or 12-Card configurations
- Available with gas tube terminal protection
- Made in USA



Semi-Buried Pedestal (Type-07)



Open Front

DATA SHEET

www.fiberopticlink.com

Ordering Information

| Description | Housing | Part Number |
|--|-----------------|----------------|
| H48" x W36" x L24" with 3/4" Fire Retardant Plywood Backboard | Empty Backboard | 8806-1285-07 |
| H48" x W36" x L24" with 3/4" Fire Retardant Plywood Backboard with 5 Card Housing | 8806-1231-03 | 8806-1409-07NT |
| H48" x W36" x L24" with 3/4" Fire Retardant Plywood Backboard with 8 Card Housing | 8806-1229-03 | 8806-1406-07NT |
| H48" x W36" x L24" with 3/4" Fire Retardant Plywood Backboard with 12 Card Housing | 8806-1230-03 | 8806-1408-07NT |

Key Specifications

| | |
|------------------------|--|
| Construction: | GR-13 compliant all-dielectric LLDPE molded plastic with metal backboard frame |
| Mounting Style: | Semi-buried, 36" X 24" approximate footprint |
| Included: | Pre-wired, gel filled, snap-lock 25 pair copper terminal, feedback loop clip, ground lug with attaching hardware |
| Options: | 2-Card Fiber Optic Link housing, 5-, 8-, or 12-Card Fiber Optic Link shelf, Gas Tube Protection |

Contact

| | | |
|---|---|------------------------------|
| By Mail: | Att: Sales RLH Industries, Inc. 936 N. Main St. Orange, CA 92867 | |
| By Phone: Sales / Service Mon - Fri, 6am - 6pm, PST | Local | 714-532-1672 |
| | Toll Free | 800-877-1672 866-DO-FIBER |
| | By Email: info@fiberopticlink.com | |
| By FAX: | 714-532-1885 | |

Tech Support

| | | |
|-----------|----------------------------|------------------------------|
| By Email: | support@fiberopticlink.com | |
| By Phone: | Toll Free | 855-754-2497 855-RLH-24X7 |