

Ethernet Product Family

Media Converters

Single Channel Fiber Link Cards

- Line Powered
- Temperature hardened
- Available in 10/100M or Gigabit models
- Card fits in any RLH card housing
- Fiber distances up to 120km/74 miles

10/100M Slimline Media Converter

- Temperature hardened
- DIN rail mount
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles

Gigabit Ethernet Media Converter

- Temperature hardened
- DIN/Wall mount
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles



Power Over Ethernet Products

4+1 Port Ethernet Switch with PoE

- Temperature hardened, DIN mount
- Four 10/100M Ethernet ports with PoE
- One fiber port
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles

5 Port Ethernet Switch with PoE

- Temperature hardened, DIN mount
- Five 10/100M Ethernet ports
- PoE injection on four ports

4+2 Port Ethernet Switch with PoE

- Temperature hardened, DIN mount
- Four 10/100M Ethernet ports with PoE
- Two fiber ports
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles



DIN Mount Ethernet Switches

5 Port Ethernet Switch

- Temperature hardened
- SlimLine DIN mount
- Five 10/100M Ethernet ports

3+2 Ethernet Fiber Switch

- Temperature hardened
- SlimLine DIN mount
- Three 10/100 Ethernet Ports
- Two fiber ports
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles

4+1 Ethernet Fiber Switch

- Temperature hardened
- SlimLine DIN mount
- Four 10/100 Ethernet Ports
- One fiber port
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles



4+4 Managed Ethernet Fiber Switch

- Temperature hardened, DIN mount
- Dual redundant power inputs
- 4 10/100 UTP Ports, four 1x9 fiber ports
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles



Rack Mount Ethernet Switches

12+12 Managed Ethernet Fiber Switch

- 1RU 19" rack mount chassis
- Internal 110/220VAC power supply
- 12 RJ-45 Ethernet ports
- 12 1x9 fiber ports
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles

16+8 Managed Ethernet Fiber Switch

- 1RU 19" rack mount chassis
- Internal 110/220VAC power supply
- 16 RJ-45 Ethernet ports
- 8 1x9 fiber ports
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles

20+4 Managed Ethernet Fiber Switch

- 1RU 19" rack mount chassis
- Internal 110/220VAC power supply
- 20 RJ-45 Ethernet ports
- 4 1x9 fiber ports
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles

22+2 Managed Ethernet Fiber Switch

- 1RU 19" rack mount chassis
- Internal 110/220VAC power supply
- 22 RJ-45 Ethernet ports
- 2 1x9 fiber ports
- Dual fiber and single fiber models
- Fiber distances up to 120km/74 miles



Mode Converter

Gigabit Mode Converter

- Temperature hardened
- Ideal for critical, high voltage, remote or un-manned locations that must remain operating 24/7/365
- DIN/Wall mount
- Converts single mode to multimode and vice versa.



Please visit our web site or contact your RLH Sales Representative for additional information